



We help ideas meet the real world



Retrosign GR3

Specifications

Optical specifications GR3 ASTM

Geometry:	ASTM-E-1709
- Entrance angle	-4°
- Observation angle	0.2°, 0.5°, 1.0°
Field measurement, Ø:	30 mm / 1.2 in. and 15 mm / 0.6 in.
Spectral responsivity:	
Illuminant A and V(λ) efficiency according to ASTM	
E1709 section 6.4.2. for selected filters.	
Range (cd·lx ⁻¹ ·m ⁻²):	0-2000

Optical specifications GR3 CEN

Geometry:	EN 12899-1
- Entrance angle	5°
- Observation angle	0.33°, 0.5°, 1.0°
Field measurement, Ø:	30 mm / 1.2 in. and 15 mm / 0.6 in.
Spectral responsivity:	
Illuminant A and V(λ) efficiency according to ASTM	
E1709 section 6.4.2. for selected filters.	
Range (cd·lx ⁻¹ ·m ⁻²):	0-2000

Instrument dimensions

Length:	295 mm / 11.6 inch
Width:	83 mm / 3.3 inch
Height:	324 mm / 12.8 inch
Weight:	2.1 kg / 4.6 lbs

Electrical characteristics

EMC:	EN50081-1 / EN50082-1
RFID tag reader:	HF (13.56 MHz; ISO 15693 and ISO 1443A/B)
Power supply:	Rechargeable and replaceable Nickel Metal Hydride 9.6 V
External charger:	
- main:	230 V / 50 Hz
- optional:	110 V / 60 Hz
- charge time:	approx. 15 minutes
Data memory:	> 250,000 measurements
Interface:	USB

Environmental specification

Temperature:	
• Operating	0°C to +50°C / 32°F to 122°F
• Storage	-15°C to +55°C / 5°F to 131°F
Humidity:	non condensing

Timing

Measurement time:	3 sec.
-------------------	--------

SignTag™ RFID disc

SignTag™ Diameter:	30 mm / 1.2 in.
Thickness	3.2 mm/0.13 in.
Diameter	5 mm/ 0.2 in.

Standard delivery

Carrying case
Calibration standard
RSC 3 program
Battery charger
Ø15 aperture reducer
Small supporting plate
Lens cover
Communication cable
Quick guide
User manual on CD/DVD

Options

Extension Pole Kit, 1.5-2.7 m / 4.9-8.9 feet
Fast 12 V powered battery charger
Extra battery
Ø10 aperture
Calibration certificate
Calibration service
Lens attachment for additional entrance angles of 30° and 40°
Bluetooth
RFID reader
High precision GPS unit